

						
	HT503	HT801	HT802	HT812	HT814	HT818
Telephone Interfaces	One FXS Port, One FXO Port	One FXS Port	Two FXS Ports	Two FXS Ports	Four FXS Ports	Eight FXS Ports
Network Interfaces	Two 10/100Mbps Ports	One 10/100Mbps Port	One 10/100Mbps Port	Two 10/100/1000Mbps Ports	Two 10/100/1000Mbps Ports	Two 10/100/1000Mbps Ports
SIP Profiles	Two	Two	Two	Two	Two	Two
Fax Over IP	Yes, T.38 Fax	Yes, T.38 Fax	Yes, T.38 Fax	Yes, T.38 Fax	Yes, T.38 Fax	Yes, T.38 Fax
Security	SIPS/TLS, SRTP, HTTPS	SIPS/TLS, SRTP, HTTPS, AES	SIPS/TLS, SRTP, HTTPS, AES	SIPS/TLS, SRTP, HTTPS, AES	SIPS/TLS, SRTP, HTTPS, AES	SIPS/TLS, SRTP, HTTPS, AES
Audio Conferencing	3-Way	3-Way	3-Way	3-Way	3-Way	3-Way
Zero Config	Yes	Yes	Yes	Yes	Yes	Yes
Provisioning	HTTP, HTTPS, TFTP, TR-069	HTTP, HTTPS, TFTP, TR-069	HTTP, HTTPS, TFTP, TR-069	HTTP, HTTPS, TFTP, TR-069	HTTP, HTTPS, TFTP, TR-069	HTTP, HTTPS, TFTP, TR-069
NAT Router	Yes	No	No	Yes (100Mbps routing speed)	Yes (100Mbps routing speed)	Yes (100Mbps routing speed)
Short / Long Haul	REN 3: 150 ft on 24 AWG lines	2 Ren: 1km on 24AWG Line	2 Ren: 1km on 24AWG Line	3 Ren: 1km on 24AWG Line	2 Ren: 1km on 24AWG Line	2 Ren: 1km on 24AWG Line
Codecs	G.711, G.723.1, G.729 A/B/E, G.726, iLBC	G.711, G.723.1, G.729 A/B, G.726, iLBC, OPUS	G.711, G.723.1, G.729 A/B, G.726, iLBC, OPUS	G.711, G.723.1, G.729 A/B, G.726, iLBC, OPUS	G.711, G.723.1, G.729 A/B, G.726, iLBC, OPUS	G.711, G.723.1, G.729 A/B, G.726, iLBC, OPUS
Flash Size	4MB	16MB	16MB	16MB	16MB	128MB
Memory Size	16MB	32MB	32MB	128MB	128MB	256MB
Unique Security Certificate per Unit	No	Yes	Yes	Yes	Yes	Yes
Call Feature Support	Advanced Call Features	Advanced Call Features	Advanced Call Features	Advanced Call Features	Advanced Call Features	Advanced Call Features