



Infrared Weatherproof Dome Camera GSC3610

The GSC3610 is a weatherproof infrared (IR) ceiling-mounted fixed dome IP camera with a 3.6mm lens - making it an ideal device for wide-angle monitoring of nearby subjects in environments such as banks, hotels, retail stores, offices, warehouses, and building entrances. This device supports motion detection and smart infrared technology for white balance and exposure to monitor activity at night in outdoor or dark enclosed spaces. The GSC3610 can be managed with GSURF Pro, Grandstream's free video management software, along with other ONVIF-compliant video management systems. It pairs with Grandstream's video phones and GSC3570 HD intercom and facility control station for active end-point monitoring and facility control. By adding weatherproof capabilities, this is an ideal device for increasing security and facility management in any indoor or outdoor area.



Supports motion detection



Smart infrared technology for optimal white balance and exposure



Built-in PoE to power the device and provide a network connection



Supports alert notifications via outbound voice or video call & email screenshot



IP66-level weatherproof capability



Primary stream 1920x1080 and Secondary stream 640x480



SIP/VoIP support for video and audio streaming to endpoints (external microphone required)

Network Protocol	SIP RFC3261, TCP/IP/UDP, RTP/RTCP, HTTP/HTTPS, ARP, ICMP, DNS (A record, SRV, NAPTR), DHCP, SSH, TFTP, NTP, STUN, LLDP-MED, TLS, SRTP
Image Sensor Resolution	1/2.9" CMOS Sensor, 1920(H)*1080(V)
Video Compression	H.264/H.265/JPEG/MJPEG
Supported Maximum Video Resolution and Frame Rate	Primary Stream:1920*1080 Secondary Stream: 640*480
Video Output	Network
Audio	Line-In: 1 x 3.5mm, 1-50mVpp; Line-Out: 1 x 3.5mm, 560Ω, 4.0Vpp
Scanning System	Progressive
Image Configuration	Saturation/Brightness/Contrast/Sharpness, White Balance
Focal Length	Fixed 3.6mm
Infrared LED	2x LED, up to 20M, Auto Control
Ethernet	One RJ-45 (10/100Base-T) Port with PoE
ONVIF	Yes, Profile S
Day/Night	Color/ Black &White (IR-CUT)
Motion Detection	Supported
Language Supported	Multi-Language
Privacy Mask	4 Rectangular Zone
Weatherproof Grade	Metal , IP66-level weatherproof capability
Power	DC12V±10%,1A (Power Adapter NOT Included) PoE: Support IEEE 802.3af
Temperature / Humidity	-20 °C ~ 50 °C, RH95% Max
Weight and Dimensions	109 x 93mm, 390g
Compliance	FCC, CE, RCM, IC